

HERTALAN® EPDM STRIPS (EN 14909)

HERTALAN® EPDM STRIPS are used as waterproof membranes in new constructions around window casings and cavity walls. All seams and connections are possible with HERTALAN® EPDM STRIPS and they can be installed to create an impermeable seal. HERTALAN® EPDM STRIPS have a very simple application method and are available in a variety of widths up to 1300 mm.

HERTALAN® EPDM STRIPS			
Length	20 m	Polymer	EPDM
Width	100 – 1300 mm	Colour	Black
Thickness	0,75 / 1,0 / 1,2 mm	Mass	1,23 kg/m ² per mm

Characteristic and test method		Specifications	Value or statement
Appearance (EN1850-2)		Comply	Complies
Straightness of the edges (EN1848-2)	mm	≤ 30	Complies
Flatness (EN1848-2)	mm	≤ 10	Complies
Nail shank (l/t) (EN 12310-1)*	N	> 100	120
Ageing (EN 1296 / EN 1928)	-	Comply	Complies
Shear resistance of joints (EN 12317-2)	N/50mm	≥ 200	282
Fire resistance (EN 13501-1)	-	Class E	Class E
Resistance against static load (EN 12730)*	kg	≥ 25	25
Impact resistance (EN 12691)*	mm	≥ 300	300
Watertightness (EN 1928)	-	Watertight	Complies
Durability (alkali) (EN 1847 / EN 1928)	-	Comply	Complies
Water vapour transmission properties (EN 1931)	-	70.000	70.000